


MULTIMAX MP 527

TIRE SIZE	500/70 R 24 IND
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	COMPACT LOADER / TELEHANDLER / COMPACT LOADER / TELEHANDLER
VERSION	STANDARD
TL/TT	TL
LI/SS	164 A8/B



DIMENSIONS IS STANDARD

SW (MM)	503	RIM REC	DW 16 L
OD (MM)	1310	RIM ALT	DW 15 L ; DW 18 L
SLR (MM)	597	ECE	E4-106R-002658
RC (MM)	4019	SRI	625

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	2400	2850	3250	3700	4150	4450	5000	-	-
40	2400	2850	3250	3700	4150	4450	5000	-	-
30	2570	3050	3480	3960	4445	4765	5350	-	-
25	2665	3165	3610	4110	4610	4940	5550	-	-
10 CYC.	2925	3600	4240	4875	5550	6040	6825	7200	7500
STATIC	4485	5520	6500	7475	8510	9260	10465	11040	11500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.