

# AGRIMAX RT 765

|                  |                                                                                 |
|------------------|---------------------------------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>420/70 R 28</b>                                                              |
| <b>UM</b>        | IS STANDARD                                                                     |
| <b>MACHINERY</b> | PULVERIZADOR / TRACTOR /<br>VENDIMIADORA / COSECHADORA /<br>MAQUINARIA AGRÍCOLA |
| <b>VERSIÓN</b>   | SPECIAL                                                                         |
| <b>TIRE TYPE</b> | TL                                                                              |
| <b>LI/SS</b>     | 133 D                                                                           |



## DIMENSIONES IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 418  | <b>RIM REC</b> | W 13            |
| <b>OD (MM)</b>  | 1349 | <b>RIM ALT</b> | W 12 ; W 14 L   |
| <b>SLR (MM)</b> | 604  | <b>ECE</b>     | E11-106R-005520 |
| <b>RC (MM)</b>  | 4020 | <b>SRI</b>     | 650             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR   | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|--------------|------|------|------|------|------|------|
| <b>65</b>    | 1135 | 1320 | 1505 | 1690 | 1875 | 2060 |
| <b>50</b>    | 1195 | 1390 | 1585 | 1780 | 1975 | 2165 |
| <b>40</b>    | 1245 | 1450 | 1650 | 1855 | 2060 | 2260 |
| <b>30</b>    | 1305 | 1520 | 1735 | 1945 | 2160 | 2370 |
| <b>10 LT</b> | 1525 | 1770 | 2020 | 2270 | 2520 | 2765 |
| <b>10 HT</b> | 1305 | 1520 | 1735 | 1945 | 2160 | 2370 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.