

# AGRIMAX RT 855

|                  |                                                                       |
|------------------|-----------------------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>420/85 R 34</b>                                                    |
| <b>UM</b>        | US STANDARD                                                           |
| <b>MACHINERY</b> | SPRAYER / VINEYARD HARVESTER /<br>TRACTOR / HARVESTER /<br>IMPLEMENTS |
| <b>VERSION</b>   | SPECIAL                                                               |
| <b>TL/TT</b>     | TL                                                                    |
| <b>LI/SS</b>     | 142 A8/B                                                              |



## DIMENSIONS US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94033133 | <b>RC (IN)</b> | 185.1          |
| <b>SW (IN)</b>  | 17.2     | <b>RIM REC</b> | W 15 L         |
| <b>OD (IN)</b>  | 62.1     | <b>RIM ALT</b> | W 13 ; W 14 L  |
| <b>SLR (IN)</b> | 27.9     | <b>ECE</b>     | E4-106R-000656 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI   | 9    | 12   | 15   | 17   | 20   | 23   |
|-------------|------|------|------|------|------|------|
| <b>30</b>   | 3220 | 3750 | 4270 | 4790 | 5320 | 5840 |
| <b>25</b>   | 3220 | 3750 | 4270 | 4790 | 5320 | 5840 |
| <b>20</b>   | 3450 | 4010 | 4570 | 5140 | 5700 | 6260 |
| <b>5 LT</b> | 4320 | 5030 | 5730 | 6440 | 7140 | 7840 |
| <b>5 HT</b> | 3450 | 4010 | 4570 | 5140 | 5700 | 6260 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.