

FLOTATION 648

TIRE SIZE	500/50 - 17
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	ENFARDADEIRA DE FENO / CEIFEIRA / ESPALHADOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	128 A8/124 B
LI/SS FREE ROLLING	140 A8/136 B



DIMENSÕES US STANDARD

CÓDIGO USA	94039814	RC (IN)	108.3
SW (IN)	20.1	RIM REC	16.00
OD (IN)	37.2	ECE	E4-106R-002713
SLR (IN)	16.4	PR	10

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	22	25	29
5 FR	6530	7020	7720
10 FR	5870	6320	6940
20 FR	5220	5620	6170
25 FR	4660	5020	5510
30 FR	4200	4520	4940
5 DW	4700	5050	5560
10 DW	4220	4540	5000
20 DW	3750	4030	4440
25 DW	3350	3600	3970
30 DW	3020	3240	3530

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.