

# FLOTATION 648

<b>TIRE SIZE</b>	<b>600/55 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ENFARDADEIRA DE FENO / CEIFEIRA / ESPALHADOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	DUAL BEAD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	160 A8/156 B
<b>LI/SS FREE ROLLING</b>	173 A8/169 B



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94045280	<b>RC (IN)</b>	146.3
<b>SW (IN)</b>	23.6	<b>RIM REC</b>	AG 20.00
<b>OD (IN)</b>	48.4	<b>ECE</b>	E11-106R-004393
<b>SLR (IN)</b>	21.3	<b>PR</b>	20

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	44	45	46
<b>5 FR</b>	19320	19690	20060
<b>10 FR</b>	17390	17720	18050
<b>20 FR</b>	15450	15750	16050
<b>25 FR</b>	13800	14060	14330
<b>30 FR</b>	12420	12650	12790
<b>5 DW</b>	13380	13620	13890
<b>10 DW</b>	12040	12270	12500
<b>20 DW</b>	10700	10900	11110
<b>25 DW</b>	9560	9730	9920
<b>30 DW</b>	8600	8760	8820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.