


# RM 500

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>500/70 R 24</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | HARVESTER  |
| <b>VERSION</b>      | STEEL BELTED   |
| <b>TL/TT</b>        | TL   |
| <b>LI/SS</b>        | 167 A8 ; 155 A8  |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 502  | <b>RIM REC</b> | W 16 L          |
| <b>OD (MM)</b>  | 1310 | <b>RIM ALT</b> | W 15 L          |
| <b>SLR (MM)</b> | 572  | <b>ECE</b>     | E11-106R-005989 |
| <b>RC (MM)</b>  | 3907 | <b>SRI</b>     | 625             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR             | 0.8  | 1.0  | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  |
|------------------------|------|------|------|------|------|------|------|
| <b>40 FREE ROLLING</b> | 2290 | 2620 | 2945 | 3600 | 4145 | 4800 | 5450 |
| <b>40 DRIVE WHEEL</b>  | 1630 | 1860 | 2095 | 2560 | 3945 | 3410 | 3875 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.