


# EARTHMAX SR 47

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>18.00 R 33</b>  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | RIGID DUMP TRUCK   |
| <b>VERSION</b>      | CUT RESISTANT COMPOUND   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 195 B  |



## DIMENSIONS IS STANDARD

|                 |           |                    |     |
|-----------------|-----------|--------------------|-----|
| <b>OD (MM)</b>  | 1885      | <b>TRA CODE</b>    | E4  |
| <b>SLR (MM)</b> | 867       | <b>STAR RATING</b> | ★★★ |
| <b>RC (MM)</b>  | 5674      |                    |     |
| <b>RIM REC</b>  | 13.00/2.5 |                    |     |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 7.25  | 7.50  | 7.75  | 8.00  |
|------------|-------|-------|-------|-------|
| 50         | 11200 | 11500 | 11800 | 12150 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.