

AGRIMAX RT 945

| | |
|---------------------|--|
| TIRE SIZE | 380/90 R 50 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ОПРЫСКИВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 151 A8/B |



РАЗМЕРЫ IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 380 | RIM REC | W 12 |
| OD (MM) | 1954 | RIM ALT | W 11; W 13 |
| SLR (MM) | 906 | ECE | E4-106R-001487 |
| RC (MM) | 5900 | SRI | 925 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 |
|------------|------|------|------|------|------|------|
| 50 | 1865 | 2415 | 2970 | 3210 | 3450 | - |
| 40 | 1865 | 2415 | 2970 | 3210 | 3450 | - |
| 30 | 2000 | 2590 | 3180 | 3440 | 3695 | - |
| 10 | 2745 | 3365 | 4090 | 4765 | 5020 | 5175 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.