


AGRIMAX PROHARVEST

TYRE SIZE	VF 900/60 R 32
UM	US STANDARD
CONSTRUCTION	 RADIAL
VERSION	STEEL BELTED
TYRE TYPE	TL
LI/SS	193 D



DIMENSIONS US STANDARD

USA CODE	94514403	RC (IN)	224.9
SW (IN)	34.7	RIM REC	DW 30 B
OD (IN)	74.8	ECE	E11-106R-0010580
SLR (IN)	33.0		

LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46
45	9010	10380	11770	13380	14770	16390	18230	18460	21460	23070
FROM 40 TO 25	9890	11410	12930	14700	16230	18000	20030	20280	23580	25350
20	10090	11640	13190	15000	16560	18360	20440	20690	24050	25860
12	10280	11870	13450	15300	16880	18730	20830	21100	24530	26370
5	10880	12550	14230	16180	17860	19810	22030	22310	25940	27890
UPTO 20 CYC	11230	12950	14680	16700	18430	20440	22740	23030	26770	28780
UPTO 10 CYC	13400	15460	17530	19930	21990	24400	27150	27490	31950	34360
UPTO 5 CYC	14690	16950	19210	21850	24110	26740	29750	30120	35020	37650
10HT	10090	11640	13190	15000	16560	18360	20440	20690	24050	25860

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.