


# AGRIMAX RT 657

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>540/65 R 34</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | VINEYARD HARVESTER / TRACTOR / HARVESTER   |
| <b>VERSION</b>      | SPECIAL  |
| <b>TYRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 152 D ; 155 A8   |



## DIMENSIONS US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94062645 | <b>RC (IN)</b> | 186.7          |
| <b>SW (IN)</b>  | 20.9     | <b>RIM REC</b> | W 16 L         |
| <b>OD (IN)</b>  | 61.7     | <b>RIM ALT</b> | W 18 L         |
| <b>SLR (IN)</b> | 28.0     | <b>ECE</b>     | E4-106R-000652 |

## LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 90   | 12   | 15   | 17   | 20   | 23   | 29   | 35    |
|-----------|------|------|------|------|------|------|------|-------|
| 40        | 3760 | 4390 | 4940 | 5480 | 6030 | 6500 | 7210 | 7850  |
| 30        | 3960 | 4610 | 5180 | 5760 | 6340 | 6830 | 7570 | 8220  |
| 25        | 4100 | 4780 | 5390 | 5990 | 6580 | 7100 | 7860 | 8540  |
| 20        | 4330 | 5050 | 5680 | 6300 | 6940 | 7480 | 8290 | 9010  |
| 5 LT      | 5040 | 5890 | 6610 | 7350 | 8090 | 8720 | 9660 | 10490 |
| 5 HT      | 4330 | 5050 | 5680 | 6300 | 6940 | 7480 | 8290 | 9010  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.