


# RT 747 AGRO INDUSTRIAL

<b>TIRE SIZE</b>	<b>11L R 16</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	CHARGEUSE COMPACTE / CHARGEUSE TÉLESCOPIQUE / CHARGEUSE COMPACTE / CHARGEUSE TÉLESCOPIQUE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	122 A8/B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	290	<b>RIM REC</b>	W 8
<b>OD (MM)</b>	850	<b>RIM ALT</b>	W 10 L
<b>SLR (MM)</b>	371	<b>ECE</b>	E11-106R-005769
<b>RC (MM)</b>	2497		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.6	2.0	2.2	2.4	2.6
10	1265	1530	1790	1920	2055	2200
30	940	1165	1385	1500	1610	---
40	880	1085	1295	1395	1500	---

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.