

# TR 882

<b>TIRE SIZE</b>	<b>400/60 - 15.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	HEUPRESSE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE / ANHÄNGER / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE / ANHÄNGER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	122 A8
<b>LI/SS FREE ROLLING</b>	134 A8



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	400	<b>RIM REC</b>	AG 13.00
<b>OD (MM)</b>	875	<b>ECE</b>	E11-106R-004330
<b>SLR (MM)</b>	378	<b>PR</b>	8
<b>RC (MM)</b>	2605	<b>SRI</b>	410

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.40
10 FR	2970
25 FR	2525
30 FR	2375
40 FR	2120
10 DW	2100
25 DW	1785
30 DW	1680
40 DW	1500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.