

# AW 909

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | 10.0/75 - 15.3   |
| <b>UM</b>                 | IS STANDARD  |
| <b>CONSTRUCTION</b>       | BIAS   |
| <b>MACHINERY</b>          | ENFARDADEIRA DE FENO /<br>IMPLEMENTOS AGRÍCOLAS /<br>REBOQUE / CEIFEIRA / IMPLEMENTOS<br>AGRÍCOLAS |
| <b>VERSÃO</b>             | STANDARD   |
| <b>TIRE TYPE</b>          | TL   |
| <b>LI/SS FREE ROLLING</b> | 135 A8   |



## DIMENSÕES IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 274  | <b>RIM REC</b> | 9.00           |
| <b>OD (MM)</b>  | 760  | <b>ECE</b>     | E4-106R-001880 |
| <b>SLR (MM)</b> | 343  | <b>PR</b>      | 18             |
| <b>RC (MM)</b>  | 2227 |                |                |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 7.10 |
|------------|------|
| 10 FR      | 3050 |
| 25 FR      | 2595 |
| 30 FR      | 2440 |
| 40 FR      | 2180 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.