


AGRIMAX V- FLECTO



| | |
|--------------|--|
| TIRE SIZE | VF 600/60 R 38 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRATOR DE ALTA POTENCIA / TRATOR |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 166 D |

DIMENSÕES US STANDARD

| | | | |
|------------|----------|---------|-----------------|
| CÓDIGO USA | 94059126 | RC (IN) | 200.0 |
| SW (IN) | 23.1 | RIM REC | DW 20 B |
| OD (IN) | 66.3 | RIM ALT | DW 18 L |
| SLR (IN) | 29.8 | ECE | E11-106R-005021 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 |
|-------------------------------|------|------|-------|-------|-------|-------|-------|
| 45 | 5200 | 6050 | 7010 | 7860 | 8710 | 9570 | 10630 |
| FROM 40 TO 25 | 5720 | 6660 | 7700 | 8640 | 9580 | 10520 | 11700 |
| 20 | 5830 | 6790 | 7850 | 8810 | 9770 | 10720 | 11920 |
| 12 | 5940 | 6920 | 8000 | 8980 | 9950 | 10930 | 12150 |
| 5 | 6280 | 7320 | 8470 | 9500 | 10530 | 11560 | 12850 |
| *UPTO 5 CYC WITH FRONT LOADER | 8000 | 9310 | 10780 | 12090 | 13400 | 14720 | 16360 |
| 5 HT | 5830 | 6790 | 7850 | 8810 | 9770 | 10720 | 11920 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.