



IS standard



GROWING TOGETHER

XL GRIP PLUS



PRODUCT DATA SHEET



Bias



XL GRIP PLUS

XL GRIP PLUS (L-4) has been specially designed for loaders. Its deep tread provides high cut and puncture resistance as well as an extended tire life-cycle. XL GRIP PLUS is particularly suitable for heavy-duty service.

Technologies



Deep Tread

Performance



Cut Resistance



Durability



Heavy Duty



Stability



Traction

	Tire size	Type	TRA CODE	PR	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
Ø 25"	26.5 - 25	TL	L-4	28	-	STD	-	690	1775	815	5253	57.5	22.00/3.0	-
	26.5 - 25	TL	L-4	32	-	STD	-	690	1775	815	5253	57.5	22.00/3.0	-
	29.5 - 25	TL	L-4	32	-	STD	-	760	1915	876	5709	59.5	25.00/3.5	-
	29.5 - 25	TL	L-4	28	-	STD	-	760	1915	876	5709	59.5	25.00/3.5	-
	29.5 - 25	TL	L-4	36	-	STD	-	760	1915	876	5709	59.5	25.00/3.5	-
Ø 33"	35/65 - 33	TL	L-4	42	-	STD	-	900	2080	-	-	62.5	28.00/3.5	-

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference