


AGRIMAX SPARGO SB

TIRE SIZE	VF 380/90 R 50
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR / SPRAYER
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	175 D



DIMENSIONS US STANDARD

USA CODE	94076116	RC (IN)	235.7
SW (IN)	15.7	RIM REC	W13
OD (IN)	76.9	RIM ALT	W12;DW13
SLR (IN)	35.6	ECE	E11-106R-0010177

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	14	12	20	23	26	29	32	35	38	41	44	47	49	52	55	58	61	64
45	5970	6650	7490	8180	8590	9010	9290	9560	10050	10530	10950	11360	11710	12050	12410	12750	13300	13850
FROM 40 TO 25	6550	7310	8230	8990	9440	9890	10200	10510	11040	11570	12030	12480	12870	13240	13630	14000	14610	15220
20	6680	7460	8390	9160	9630	10100	10410	10720	11260	11810	12270	12740	13120	13510	13900	14290	14910	15520
12	6820	7610	8560	9350	9830	10300	10620	10930	11490	12040	12520	12990	13390	13780	14180	14580	15210	15830
5	7200	8040	9040	9880	10390	10880	11230	11560	12140	12720	13230	13730	14150	14570	14980	15400	16080	16740

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.