

# GF 304

|                     |                    |
|---------------------|--------------------|
| <b>TIRE SIZE</b>    | <b>18X8.50 - 8</b> |
| <b>UM</b>           | US STANDARD        |
| <b>CONSTRUCTION</b> | ❖ BIAS             |
| <b>MACHINERY</b>    | CARRO DE GOLF      |
| <b>VERSIÓN</b>      | STANDARD           |
| <b>TIRE TYPE</b>    | TL                 |



## DIMENSIONES US STANDARD

|                   |          |                |                             |
|-------------------|----------|----------------|-----------------------------|
| <b>CÓDIGO USA</b> | 94008049 | <b>RC (IN)</b> | 52.5                        |
| <b>SW (IN)</b>    | 8.5      | <b>RIM REC</b> | 7.00 I - 55; I - 70; I - 90 |
| <b>OD (IN)</b>    | 18.1     | <b>ECE</b>     | E11-106R-003442             |
| <b>SLR (IN)</b>   | 8.0      | <b>PR</b>      | 4                           |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>22</b> |
| 10               | 825       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.