


AW 726

| | |
|---------------------------|--|
| TIRE SIZE | 11.5/80 - 15.3 |
| UM | US STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | REMOLQUE / MAQUINARIA AGRÍCOLA |
| VERSIÓN | ARAMID BELTED |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 126 A8 |
| LI/SS FREE ROLLING | 139 A8 |



DIMENSIONES US STANDARD

| | | | |
|-------------------|----------|----------------|------------------|
| CÓDIGO USA | 94064366 | RC (IN) | 99.6 |
| SW (IN) | 11.8 | RIM REC | 9.00 |
| OD (IN) | 33.7 | ECE | E11-106R-0010913 |
| SLR (IN) | 14.3 | PR | 14 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 70 |
|-----------|------|
| 5 FR | 7500 |
| 15 FR | 6370 |
| 20 FR | 6000 |
| 25 FR | 5360 |
| 5 DW | 5250 |
| 15 DW | 4460 |
| 20 DW | 4200 |
| 25 DW | 3750 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.