


# AGRIMAX V- FLECTO



<b>TIRE SIZE</b>	<b>VF 710/55 R 34</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MOTORSTARK TRAKTOR / TRAKTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	170 D

## DIMENSIONER US STANDARD

<b>USA CODE</b>	94513376	<b>RC (IN)</b>	193.3
<b>SW (IN)</b>	27.9	<b>RIM REC</b>	DW 25 B
<b>OD (IN)</b>	65.3	<b>RIM ALT</b>	DW 27 B
<b>SLR (IN)</b>	28.6	<b>ECE</b>	E11-106R-0010831

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	5900	6860	7940	8910	9870	10820	12040
<b>FROM 40 TO 25</b>	6480	7540	8730	9790	10850	11900	13230
20	6600	7680	8900	9980	11060	12140	13490
12	6730	7840	9070	10170	11280	12380	13760
5	7120	8290	9600	10760	11930	13090	14550
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	9070	10550	12210	13700	15180	16670	18520
5 HT	6600	7680	8900	9980	11060	12140	13490

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.