


# AW 711

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>265/70 R 16.5</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | COSECHADORA / MAQUINARIA<br>AGRÍCOLA / COSECHADORA /<br>MAQUINARIA AGRÍCOLA              |
| <b>VERSIÓN</b>      | STUBBLE RESISTANT  |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 134 A8/B   |



## DIMENSIONES US STANDARD

|                   |          |                |                 |
|-------------------|----------|----------------|-----------------|
| <b>CÓDIGO USA</b> | 94053292 | <b>RC (IN)</b> | 90.0            |
| <b>SW (IN)</b>    | 10.4     | <b>RIM REC</b> | 8.25            |
| <b>OD (IN)</b>    | 30.4     | <b>ECE</b>     | E11-106R-002978 |
| <b>SLR (IN)</b>   | 13.5     |                |                 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12   | 17   | 23   | 29   | 35   | 41   | 46   | 52   | 58   |
|-----------|------|------|------|------|------|------|------|------|------|
| 30        | 1500 | 1970 | 2390 | 2770 | 3190 | 3600 | 3880 | 4250 | 4670 |
| 25        | 1500 | 1970 | 2390 | 2770 | 3190 | 3600 | 3880 | 4250 | 4670 |
| 20        | 1680 | 2200 | 2680 | 3100 | 3560 | 4030 | 4350 | 4770 | 5240 |
| 15        | 1790 | 2350 | 2840 | 3280 | 3790 | 4290 | 4630 | 5070 | 5570 |
| 10        | 1900 | 2480 | 3010 | 3480 | 4010 | 4540 | 4910 | 5370 | 5900 |
| 5         | 2110 | 2760 | 3340 | 3870 | 4450 | 5050 | 5450 | 5960 | 6550 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.