


AGRIMAX RT 600

TIRE SIZE	800/65 R 32
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	BIÇERDÖVER / YAYICI / TRAKTÖR / UYGULAMALI MAKINE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	176 A8 ; 173 B



BOYUTLAR US STANDARD

USA CODE	94044795	RC (IN)	218.8
SW (IN)	30.5	RIM REC	DW 27 B
OD (IN)	71.7	RIM ALT	DH 27 B ; DW 25 B
SLR (IN)	32.4	ECE	E4-106R-001428

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	23	29	35	41	44	46	52
30	7000	8070	9890	10800	11870	12930	14000	14330	-	-
25	7610	8760	10750	11740	12900	14050	15210	15650	-	-
20	8150	9380	11510	12570	13800	15050	16280	16750	-	-
5 LT	10200	11750	14410	15740	17280	18840	20390	20980	-	-
5 HT	8150	9380	11510	12570	13800	15050	16280	16750	-	-
5 CYC.	-	12470	15940	17550	20390	22350	24370	25440	26510	27420

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.