


MULTIMAX MP 522

| | |
|---------------------|--|
| TIRE SIZE | 440/80 R 24 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | CARREGADORA COMPACTA / LEVANTADOR TELESCÓPICO / CARREGADORA COMPACTA / LEVANTADOR TELESCÓPICO |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 161 A8/B |



DIMENSÕES IS STANDARD

| | | | |
|-----------------|------|----------------|-------------------------|
| SW (MM) | 441 | RIM REC | DW 14 L |
| OD (MM) | 1314 | RIM ALT | DW 13; DW 13 L; DW 15 L |
| SLR (MM) | 586 | ECE | E11-106R-002966 |
| RC (MM) | 3958 | SRI | 625 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.5 | 4.0 | 4.2 | 4.4 |
|------------|------|------|------|------|------|------|------|-------|-------|
| 50 | 2220 | 2640 | 3010 | 3425 | 3840 | 4120 | 4625 | - | - |
| 40 | 2220 | 2640 | 3010 | 3425 | 3840 | 4120 | 4625 | - | - |
| 30 | 2380 | 2825 | 3220 | 3665 | 4110 | 4410 | 4950 | - | - |
| 25 | 2465 | 2930 | 3340 | 3800 | 4265 | 4575 | 5135 | - | - |
| 10 CYC. | 2710 | 3335 | 3925 | 4515 | 5140 | 5590 | 6320 | 6665 | 6940 |
| STATIC | 4150 | 5110 | 6015 | 6920 | 7875 | 8570 | 9685 | 10215 | 10640 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.