


FL 630 SUPER

TIRE SIZE	750/45 R 26.5
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SPRIDARE / TANKBIL / SLÄPVAGN / ARBETSFORDON
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	170 D



DIMENSIONER US STANDARD

USA CODE	94046096	RC (IN)	163.3
SW (IN)	29.7	RIM REC	AG 24.00
OD (IN)	53.1	ECE	E4-106R-001652
SLR (IN)	23.9		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	23	29	35	41	46	52	58
45	3860	4400	4940	6140	6990	8070	9150	10000	10940	12040
40	4230	4830	5420	6750	7670	8860	10050	10980	12040	13230
30	5130	5850	6570	8170	9290	10720	12170	13290	14570	16000
25	5760	6580	7390	9180	10440	12060	13680	14940	16380	17990
15	6690	8580	10660	12120	14010	14010	15880	17350	19020	20900
5	7630	8700	9770	12150	13810	15960	18100	19760	21670	23810

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.