


# AGRIMAX SPARGO SB

|              |  |
|--------------|--|
| TIRE SIZE    | VF 380/90 R 46   |
| UM           | US STANDARD  |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | ТРАКТОР-ТЯГАЧ /<br>ОПРЫСКИВАТЕЛЬ   |
| VERSION      | STEEL BELTED   |
| TIRE TYPE    | TL   |
| LI/SS        | 173 D  |



## РАЗМЕРЫ US STANDARD

|          |          |         |                  |
|----------|----------|---------|------------------|
| USA CODE | 94076123 | RC (IN) | 223.1            |
| SW (IN)  | 15.7     | RIM REC | W13              |
| OD (IN)  | 72.9     | RIM ALT | W12;DW13         |
| SLR (IN) | 33.7     | ECE     | E11-106R-0010176 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI     | 14   | 12   | 20   | 23   | 26   | 29    | 32    | 35    | 38    | 41    | 44    | 47    | 49    | 52    | 55    | 58    | 61    | 64    |
|---------------|------|------|------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45            | 5620 | 6270 | 7050 | 7700 | 8100 | 8480  | 8750  | 9010  | 9460  | 9930  | 10310 | 10710 | 11030 | 11360 | 11680 | 12010 | 12530 | 13040 |
| FROM 40 TO 25 | 6170 | 6880 | 7740 | 8460 | 8890 | 9320  | 9610  | 9890  | 10400 | 10900 | 11330 | 11750 | 12120 | 12470 | 12840 | 13190 | 13760 | 14330 |
| 20            | 6300 | 7030 | 7910 | 8640 | 9080 | 9510  | 9800  | 10090 | 10610 | 11120 | 11560 | 12000 | 12360 | 12720 | 13090 | 13450 | 14040 | 14620 |
| 12            | 6420 | 7160 | 8060 | 8800 | 9250 | 9690  | 9990  | 10290 | 10820 | 11340 | 11790 | 12230 | 12600 | 12980 | 13350 | 13720 | 14310 | 14910 |
| 5             | 6780 | 7580 | 8530 | 9310 | 9780 | 10260 | 10580 | 10880 | 11440 | 11990 | 12460 | 12930 | 13330 | 13730 | 14110 | 14510 | 15140 | 15770 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.