DATA SHEET

PRINTED ON
23-04-2026

TR 135

TIRE SIZE	**8.3 - 24**
UM	IS STANDARD
CONSTRUCTION	BIAS
MACHINERY	TRACTOR / REMORCĂ
VERSION	HD
TIRE TYPE	TT
LI/SS	111 A6

DIMENSIUNI IS STANDARD

SW (MM)	211	**RIM REC**	W 7
OD (MM)	995	**RIM ALT**	W 6
SLR (MM)	469	**PR**	10
RC (MM)	2985	**TRA CODE**	R1

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	4.00
30	1090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..