

# EARTHMAX SR 431

|                  |                        |
|------------------|------------------------|
| <b>TIRE SIZE</b> | <b>16.00 R 25</b>      |
| <b>UM</b>        | US STANDARD            |
| <b>MACHINERY</b> | RIGID DUMP TRUCK       |
| <b>VERSION</b>   | CUT RESISTANT COMPOUND |
| <b>TL/TT</b>     | TL                     |
| <b>LI/SS</b>     | 177 B                  |



## DIMENSIONS US STANDARD

|                 |          |                                      |           |
|-----------------|----------|--------------------------------------|-----------|
| <b>USA CODE</b> | 94073597 | <b>RIM REC</b>                       | 11.25/2.0 |
| <b>OW (IN)</b>  | 17.8     | <b>TRA CODE</b>                      | E4        |
| <b>OD (IN)</b>  | 60.3     | <b>STAR RATING</b>                   | ★★        |
| <b>SLR (IN)</b> | 28.1     | <b>TREAD DEPTH (32<sup>nd</sup>)</b> | 56.7      |
| <b>RC (IN)</b>  | 183.0    | <b>TMPH (IS) (TKM/H)</b>             | 114       |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 73    | 76    | 80    | 83    | 87    | 91    | 94    | 98    | 102   |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30        | 12300 | 12800 | 13200 | 13900 | 14300 | 14800 | 15200 | 15700 | 16100 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.