

# AW 909

<b>TIRE SIZE</b>	11.5/80 - 15.3
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	139 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94010646	<b>RC (IN)</b>	97.4
<b>SW (IN)</b>	11.8	<b>RIM REC</b>	9.00
<b>OD (IN)</b>	33.2	<b>ECE</b>	E4-106R-001897
<b>SLR (IN)</b>	14.6	<b>PR</b>	14

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	69
5 FR	7500
15 FR	6370
20 FR	6000
25 FR	5360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.