


# TR 461

<b>TIRE SIZE</b>	<b>12.5/80 - 18</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	TELESKOPLASTARE / GRÄVLASTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	129 A8
<b>LI/SS FREE ROLLING</b>	142 A8



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	305	<b>RIM REC</b>	W 9
<b>OD (MM)</b>	987	<b>RIM ALT</b>	11
<b>SLR (MM)</b>	435	<b>ECE</b>	E11-106R-005367
<b>RC (MM)</b>	2902	<b>PR</b>	12

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>3.70</b>
<b>10 FR</b>	3710
<b>25 FR</b>	3155
<b>30 FR</b>	2970
<b>40 FR</b>	2650
<b>10 DW</b>	2590
<b>25 DW</b>	2200
<b>30 DW</b>	2070
<b>40 DW</b>	1850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.