


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>320/85 R 28</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZATOR / MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	124 A8/B



## DIMENSIUNI IS STANDARD

<b>SW (MM)</b>	329	<b>RIM REC</b>	W 11
<b>OD (MM)</b>	1255	<b>RIM ALT</b>	W 9; W 10
<b>SLR (MM)</b>	569	<b>ECE</b>	E4-106R-000615
<b>RC (MM)</b>	3743	<b>SRI</b>	600

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
50	880	1025	1170	1315	1460	1600
40	880	1025	1170	1315	1460	1600
30	945	1100	1255	1410	1565	1715
10 LT	1180	1375	1570	1760	1955	2145
10 HT	945	1100	1255	1410	1565	1715

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.