DATA SHEET

Latest update
2-06-2026

AGRIMAX TURF RT 333

TYRE SIZE	**480/70 R 28**
UM	US STANDARD
CONSTRUCTION	RADIAL
MACHINERY	TRACTOR
VERSION	STANDARD
TL/TT	TL
LI/SS	140 A8 ; 140 B

DIMENSIONS US STANDARD

USA CODE	94075393	**RC (IN)**	166.5
SW (IN)	18.9	**RIM REC**	W 15 L
OD (IN)	55.9	**RIM ALT**	W 14 L ; W 16 L
SLR (IN)	24.8	**ECE**	E11-106R-009049

LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23
30	3040	3530	4030	4520	5020	5520
25	3040	3530	4030	4520	5020	5520
20	3260	3790	4310	4840	5370	5900
5 LT	4070	4730	5410	6070	6730	7390
5 HT	3260	3790	4310	4840	5370	5900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..