

# AW 909

<b>TIRE SIZE</b>	<b>10.0/80 - 12</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	121 A8



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	264	<b>RIM REC</b>	9.00
<b>OD (MM)</b>	710	<b>RIM ALT</b>	7.0
<b>SLR (MM)</b>	313	<b>ECE</b>	E4-106R-002662
<b>RC (MM)</b>	2080	<b>PR</b>	10

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.90
10 FR	2030
25 FR	1725
30 FR	1625
40 FR	1450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.