


RIDEMAX IT 696

| | |
|---------------------|--|
| TIRE SIZE | 400/80 R 24 IND |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 149 A8 ; 144 D |



DIMENSIUNI US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94038640 | RC (IN) | 148.0 |
| SW (IN) | 15.9 | RIM REC | DW 13 |
| OD (IN) | 49.2 | RIM ALT | W 12; W 14 L |
| SLR (IN) | 22.0 | ECE | E4-106R-002400 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 17 | 23 | 29 | 35 | 41 | 46 |
|-----------|------|------|------|------|------|------|
| 40 | 2900 | 3580 | 4200 | 4870 | 5490 | 6170 |
| 30 | 3170 | 3910 | 4590 | 5320 | 6010 | 6750 |
| 25 | 3370 | 4160 | 4870 | 5670 | 6380 | 7160 |
| 20 | 3510 | 4320 | 5070 | 5890 | 6640 | 7450 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.