


# EARTHMAX SR 51

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>23.5 R 25</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | BULDÓCER / PALA CARGADORA  |
| <b>VERSIÓN</b>      | CUT RESISTANT COMPOUND   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 201 A2   |



## DIMENSIONES US STANDARD

|                   |          |                    |           |
|-------------------|----------|--------------------|-----------|
| <b>CÓDIGO USA</b> | 94069828 | <b>RIM REC</b>     | 19.50/2.5 |
| <b>OD (IN)</b>    | 65.4     | <b>TRA CODE</b>    | L5        |
| <b>SLR (IN)</b>   | 29.3     | <b>STAR RATING</b> | ★★        |
| <b>RC (IN)</b>    | 192.2    |                    |           |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 76    | 80    | 83    | 87    | 91    | 94    |
|-----------|-------|-------|-------|-------|-------|-------|
| 5         | 27600 | 28300 | 29100 | 30000 | 30900 | 32000 |
| MPH / PSI | 0     |       |       |       |       |       |
| 0         | 0     |       |       |       |       |       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.