

AGRIMAX V- FLECTO

VF 710/60 R 30

| | |
|--------------|--|
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | YÜKSEK GÜÇTE TRAKTÖR / TRAKTÖR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| | 171 D |



UNDEFINED IS STANDARD

| | | | |
|----------|------|---------|------------------|
| SW (MM) | 720 | RIM REC | DW 25 B |
| OD (MM) | 1625 | RIM ALT | DW 24 B; DW 27 B |
| SLR (MM) | 701 | ECE | E11-106R-0010832 |
| RC (MM) | 4801 | SRI | 775 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 |
|--------------------------------|------|------|------|------|------|------|------|
| 70 | 2740 | 3185 | 3690 | 4140 | 4585 | 5035 | 5595 |
| FROM 65 TO 40 | 3010 | 3505 | 4055 | 4550 | 5040 | 5535 | 6150 |
| 30 | 3070 | 3570 | 4135 | 4635 | 5140 | 5640 | 6270 |
| 20 | 3130 | 3645 | 4220 | 4730 | 5240 | 5755 | 6395 |
| 10 | 3310 | 3855 | 4460 | 5005 | 5545 | 6085 | 6765 |
| *UPTO 10 CYC WITH FRONT LOADER | 4215 | 4905 | 5680 | 6370 | 7060 | 7745 | 8610 |
| 10HT | 3070 | 3570 | 4135 | 4635 | 5140 | 5640 | 6270 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.