

## RT 857

|                  |                    |
|------------------|--------------------|
| <b>TIRE SIZE</b> | <b>420/85 R 30</b> |
| <b>UM</b>        | US STANDARD        |
| <b>MACHINERY</b> | TRATTORE           |
| <b>VERSIONE</b>  | STANDARD           |
| <b>TIRE TYPE</b> | TL                 |
| <b>LI/SS</b>     | 140 A8/B           |

### DIMENSIONI US STANDARD

|                   |          |                |                |
|-------------------|----------|----------------|----------------|
| <b>CODICE USA</b> | 94044566 | <b>RC (IN)</b> | 173.1          |
| <b>SW (IN)</b>    | 17.7     | <b>RIM REC</b> | W 15 L         |
| <b>OD (IN)</b>    | 58.1     | <b>RIM ALT</b> | W 14 L ; W 13  |
| <b>SLR (IN)</b>   | 25.8     | <b>ECE</b>     | E4-106R-001394 |

### LOAD CAPACITY (LBS/TIRE)

| MPH / PSI  | 9    | 12   | 15   | 17   | 20   | 23   |
|------------|------|------|------|------|------|------|
| <b>30</b>  | 3030 | 3530 | 4020 | 4520 | 5020 | 5510 |
| <b>25</b>  | 3030 | 3530 | 4020 | 4520 | 5020 | 5510 |
| <b>20</b>  | 3250 | 3780 | 4310 | 4840 | 5370 | 5900 |
| <b>5LT</b> | 4070 | 4730 | 5400 | 6060 | 6720 | 7390 |
| <b>5HT</b> | 3250 | 3780 | 4310 | 4840 | 5370 | 5900 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

