DATA SHEET

PRINTED ON
23-04-2026

PL 801

TIRE SIZE	**6.00 - 9**
UM	IS STANDARD
CONSTRUCTION	BIAS
MACHINERY	RANGHINATORE / MIETITREBBIA / CARRELLO ELEVATORE / MIETITREBBIA / ATTREZZI AGRICOLI / CARRELLO ELEVATORE
VERSIONE	SPECIAL
TIRE TYPE	TT

DIMENSIONI IS STANDARD

SW (MM)	157
OD (MM)	543
RIM REC	4.00 E
PR	10

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	8.50
25 LOAD WHEEL	1715
25 STEER WHEEL	1320
10 OTHER VEHICLES	1715
25 OTHER VEHICLES	1320
STATIC SIDE LOADER	1995

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..