


# AGRIMAX V- FLECTO

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>VF 900/65 R 46</b>  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRATTORE A ELEVATA POTENZA /<br>TRATTORE   |
| <b>VERSIONE</b>     | SPECIAL  |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 193 D  |



## DIMENSIONI IS STANDARD

|                 |      |                |                  |
|-----------------|------|----------------|------------------|
| <b>SW (MM)</b>  | 920  | <b>RIM REC</b> | DW 30B           |
| <b>OD (MM)</b>  | 2315 | <b>ECE</b>     | E11-106R-0011166 |
| <b>SLR (MM)</b> | 1003 | <b>SRI</b>     | 1100             |
| <b>RC (MM)</b>  | 6886 |                |                  |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR           | 0.6  | 0.8   | 1.0   | 1.2   | 1.4   | 1.6   | 2.0   |
|----------------------|------|-------|-------|-------|-------|-------|-------|
| 70                   | 5335 | 6170  | 7010  | 7950  | 8685  | 9415  | 10465 |
| <b>FROM 65 TO 40</b> | 5865 | 6785  | 7705  | 8740  | 9545  | 10350 | 11500 |
| 30                   | 5980 | 6920  | 7855  | 8910  | 9735  | 10555 | 11730 |
| 20                   | 6095 | 7055  | 8010  | 9085  | 9925  | 10760 | 11960 |
| 10                   | 6450 | 7460  | 8475  | 9610  | 10495 | 11385 | 12650 |
| <b>UPTO 30 CYC</b>   | 6655 | 7695  | 8740  | 9915  | 10830 | 11745 | 13050 |
| <b>UPTO 15 CYC</b>   | 7945 | 9190  | 10435 | 11840 | 12930 | 14020 | 15580 |
| <b>UPTO 10 CYC</b>   | 8705 | 10070 | 11440 | 12975 | 14170 | 15365 | 17075 |
| 10HT                 | 5980 | 6920  | 7855  | 8910  | 9735  | 10555 | 11730 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.