


# FL 635

<b>TIRE SIZE</b>	<b>710/40 R 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PRESSE À PAILLE / MOISSONNEUSE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	161 D



## DIMENSIONS US STANDARD

<b>CODE USA</b>	94053285	<b>RC (IN)</b>	136.5
<b>SW (IN)</b>	28.6	<b>RIM REC</b>	AG 24.00
<b>OD (IN)</b>	44.9	<b>ECE</b>	E11-106R-003014
<b>SLR (IN)</b>	20.1		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	23	29	35	41	46	52	58
45	2980	3390	3810	4740	5390	6230	7050	7700	8450	9280
40	3260	3730	4190	5200	5920	6830	7750	8470	9280	10200
30	3960	4520	5070	6300	7160	8280	9390	10250	11240	12350
25	4440	5070	5690	7080	8050	9290	10550	11520	12620	13870
20	4940	5630	6320	7860	8940	10320	11710	12790	14020	15400
15	5160	5890	6610	8220	9350	10800	12260	13380	14670	16110
5	5870	6700	7530	9370	10650	12300	13950	15230	16710	18350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.