

# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>320/70 R 24</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZADOR AGRÍCOLA / TRATOR / VINDIMADORA / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	116 D



## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	319	<b>RIM REC</b>	W 10
<b>OD (MM)</b>	1094	<b>RIM ALT</b>	W 9; W 11
<b>SLR (MM)</b>	502	<b>ECE</b>	E11-106R-005827
<b>RC (MM)</b>	3245	<b>SRI</b>	525

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
65	690	800	915	1025	1140	1250
50	725	845	960	1080	1200	1315
40	755	880	1005	1125	1250	1370
30	795	925	1055	1185	1315	1440
10 LT	925	1075	1225	1375	1525	1675
10 HT	795	925	1055	1185	1315	1440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.