


AS 504

| | |
|---------------------------|--|
| TIRE SIZE | 11.5/80 - 15.3 |
| UM | IS STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | TELESKOPLASTARE / ÅKERSLÄP / ARBETSFORDON / TELESKOPLASTARE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 123 A8 |
| LI/SS FREE ROLLING | 135 A8 |



DIMENSIONER IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 290 | RIM REC | 9.00 |
| OD (MM) | 867 | ECE | E4-106R-001894 |
| SLR (MM) | 380 | PR | 12 |
| RC (MM) | 2540 | SRI | 410 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 4.10 |
|------------|------|
| 10 FR | 3050 |
| 25 FR | 2595 |
| 30 FR | 2440 |
| 40 FR | 2180 |
| 10 DW | 2170 |
| 25 DW | 1845 |
| 30 DW | 1735 |
| 40 DW | 1550 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.