


# FL 635

<b>TIRE SIZE</b>	500/45 R 22.5
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / КОМБАЙН
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	136 D



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	490	<b>RIM REC</b>	AG 16.00
<b>OD (MM)</b>	1022	<b>ECE</b>	E11-106R-0010082
<b>SLR (MM)</b>	461	<b>SRI</b>	500
<b>RC (MM)</b>	3086		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.6	2.0	2.4	2.8
70	1125	1370	1555	1800	2040
65	1235	1505	1705	1975	2240
50	1495	1820	2065	2390	2715
40	1680	2045	2320	2685	3050
30	1865	2270	2575	2980	3385
25	1950	2375	2695	3120	3540
10	2220	2705	3070	3555	4035

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.