


# AGRIMAX RT 765

<b>TYRE SIZE</b>	<b>480/70 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR / IMPLEMENTS
<b>VERSION</b>	SPECIAL
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	145 D



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94063208	<b>RC (IN)</b>	199.0
<b>SW (IN)</b>	18.9	<b>RIM REC</b>	W 15 L
<b>OD (IN)</b>	66.2	<b>RIM ALT</b>	W 14 L; W 16 L
<b>SLR (IN)</b>	30.1	<b>ECE</b>	E11-106R-005832

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23
40	3520	4100	4670	5250	5820	6390
30	3690	4300	4910	5510	6120	6710
25	3860	4500	5130	5750	6380	7010
20	4050	4710	5370	6030	6690	7350
5 LT	4720	5790	6260	7030	7800	8580
5 HT	4050	4710	5370	6030	6690	7350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.