

XL GRIP (L3)



XL GRIP (L3)

XL GRIP (E-3/L-3) is a wide-base bias-ply tyre for loaders designed to minimize cuts and punctures in heavy-duty loading applications. It provides exceptional traction as well as an extended tyre life.



	SIZE	TT/TL	PR	LI/SS	RIM		OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
					REC RIM	ALT RIM						
												
Ø20"	16.0/70 - 20	TL	16	-	13 SDC	-	405	1090	480	3295	26,5	STD
Ø25"	17.5 - 25	TL	20	-	14.00/1.5	-	435	1345	622	3980	30,5	DB
	26.5 - 25	TL	28	-	22.00/3.0	-	680	1740	796	5150	36,5	STD
	17.5 - 25	TT	20	-	14.00/1.5	-	435	1345	622	3980	30,5	DB

DB: DUAL BEAD, STD: STANDARD, AB HD: ARAMID BELTED HD

TECHNOLOGIES		PERFORMANCES	
  E3/L3		    	

Permissible tolerances: O.D. 2%–5.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

SIZE	TT/TL	PR	LI/SS	RIM		OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
				REC RIM	ALT RIM						
											
23.5 - 25	TL	20	-	19.50/2.5	-	600	1625	742	4810	35,5	STD
29.5 - 25	TL	32	-	25.00/3.5	-	760	1860	849	5544	39	STD
20.5 - 25	TL	24	-	17.00/2.0	-	530	1485	682	4395	32,5	STD
20.5 - 25	TL	12	-	17.00/2.0	-	530	1485	682	4395	32,5	STD
26.5 - 25	TL	32	-	22.00/3.0	-	680	1740	796	5150	36,5	STD
15.5 - 25	TL	12	-	12.00/1.3	12.00/1.3 (DC)	402	1285	573	3767	25	STD
17.5 - 25	TL	16	-	14.00/1.5	-	435	1345	622	3980	30,5	STD
29.5 - 25	TL	28	-	25.00/3.5	-	760	1860	849	5544	39	STD
17.5 - 25	TL	24	-	14.00/1.5	-	435	1345	622	3980	30,5	DB

DB: DUAL BEAD, STD: STANDARD, AB HD: ARAMID BELTED HD

TECHNOLOGIES		PERFORMANCES				
						
						

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

SIZE	TT/TL	PR	LI/SS	RIM		OW (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (mm)	VERSION
				REC RIM	ALT RIM						
											
17.5 - 25	TL	20	-	14.00/1.5	-	435	1345	622	3980	30,5	STD
26.5 - 25	TL	20	-	22.00/3.0	-	680	1740	796	5150	36,5	STD
23.5 - 25	TL	16	-	19.50/2.5	-	600	1625	742	4810	35,5	STD
17.5 - 25	TL	12	-	14.00/1.5	-	435	1345	622	3980	30,5	STD
20.5 - 25	TL	20	-	17.00/2.0	-	530	1485	682	4395	32,5	STD
20.5 - 25	TL	16	-	17.00/2.0	-	530	1485	682	4395	32,5	STD
23.5 - 25	TL	24	-	19.50/2.5	-	600	1625	742	4810	35,5	AB HD
23.5 - 25	TL	24	-	19.50/2.5	-	600	1625	742	4810	35,5	STD

DB: DUAL BEAD, STD: STANDARD, AB HD: ARAMID BELTED HD

TECHNOLOGIES	PERFORMANCES
  E3/L3	    

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026



TECHNOLOGIES		PERFORMANCES				
	 E3/L3	    				
						

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.