


EARTHMAX SR 45 H2

| | |
|---------------------|--|
| TIRE SIZE | 24.00 R 35 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | САМОСВАЛ С ЖЕСТКОЙ РАМОЙ |
| VERSION | CUT RESISTANT COMPOUND |
| TIRE TYPE | TL |
| LI/SS | 209 B |



РАЗМЕРЫ IS STANDARD

| | | | |
|-----------------|-----------|--------------------|----|
| OD (MM) | 2180 | TRA CODE | E4 |
| SLR (MM) | 978 | STAR RATING | ★★ |
| RC (MM) | 6597 | | |
| RIM REC | 17.00/3.5 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 5.00 | 5.25 | 5.50 | 5.75 | 6.00 | 6.25 | 6.50 | 6.75 | 7.00 |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 50 | 14000 | 14500 | 15500 | 16000 | 16500 | 17000 | 17500 | 18000 | 18500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.