


# EARTHMAX SR 49 M

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>29.5 R 25</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | BULLDOZER / CHARGEUR-<br>TRANSPORTEUR LHD / CHARGEUR /<br>TOMBEREAU SURBAISSÉ            |
| <b>VERSION</b>      | CUT RESISTANT COMPOUND   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 200 B ; 208 A2   |



## DIMENSIONS IS STANDARD

|                 |           |                    |       |
|-----------------|-----------|--------------------|-------|
| <b>OD (MM)</b>  | 1905      | <b>TRA CODE</b>    | E4/L4 |
| <b>SLR (MM)</b> | 844       | <b>STAR RATING</b> | ★★/★  |
| <b>RC (MM)</b>  | 5600      |                    |       |
| <b>RIM REC</b>  | 25.00/3.5 |                    |       |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 4.00  | 4.25  | 4.50  | 4.75  | 5.00  | 5.25  |
|------------|-------|-------|-------|-------|-------|-------|
| 50         | 11500 | 11800 | 12500 | 12850 | 13600 | 14000 |
| 10         | 15500 | 16000 | 17000 | 17500 | 18000 | --    |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.