


# AGRIMAX TERIS

<b>TIRE SIZE</b>	<b>520/85 R 42</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	КОМБАЙН / ХЛОПКОУБОРОЧНАЯ МАШИНА
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	168 D



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94044634	<b>RC (IN)</b>	230.4
<b>SW (IN)</b>	20.3	<b>RIM REC</b>	DW 16 L
<b>OD (IN)</b>	76.8	<b>RIM ALT</b>	W15L; DW15L; DD16L; W16L; DD18L; DW18L; W18L
<b>SLR (IN)</b>	35.0	<b>ECE</b>	E4-106R-001829

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46	55
40	4080	4820	5560	6170	6920	7540	8770	10010	11240	12350	-
30	4290	5060	5840	6480	7260	7910	9200	10500	11810	12960	-
25	4460	5280	6100	6770	7580	8260	9610	10960	12310	13520	-
20	4700	5540	6390	7100	7960	8660	10090	11510	12930	14200	-
15	4840	5710	6590	7320	8200	8940	10390	11860	13330	14640	-
5	6120	7230	8330	9260	10370	11300	13150	15000	16850	18520	-
5 CYC*	-	-	-	-	-	-	-	-	-	-	20990

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.