


EARTHMAX SR 22 AS

| | |
|---------------------|--|
| TIRE SIZE | 17.5 R 25 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ÎNCĂRCĂTOR / AUTOGREDER |
| VERSION | CUT RESISTANT COMPOUND |
| TIRE TYPE | TL |
| LI/SS | 167 B ; 153 A8 ; 182 A2 |



DIMENSIUNI IS STANDARD

| | | | |
|-----------------|-----------|--------------------|----------|
| OD (MM) | 1350 | TRA CODE | E2/G2/L2 |
| SLR (MM) | 595 | STAR RATING | ★★/★/★★ |
| RC (MM) | 4010 | | |
| RIM REC | 14.00/1.5 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.25 | 1.50 | 1.75 | 2.00 | 2.25 | 2.50 | 2.75 | 3.00 | 4.00 | 4.25 | 4.50 | 4.75 | 5.00 | 5.25 | 5.50 | 5.75 | 6.00 | 6.25 |
|-------------------|-------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 50 | - | - | - | - | - | - | - | - | 4375 | 4625 | 4750 | 5000 | 5150 | 5450 | - | - | - | - |
| 40 | 1850 | 2120 | 2360 | 2650 | 2900 | 3075 | 3350 | 3650 | - | - | - | - | - | - | - | - | - | - |
| 10 | - | - | - | - | - | - | - | - | - | - | - | - | - | 7300 | 7500 | 7750 | 8000 | 8250 |
| KM/H / BAR | 6.50 | | | | | | | | | | | | | | | | | |
| 50 | - | | | | | | | | | | | | | | | | | |
| 40 | - | | | | | | | | | | | | | | | | | |
| 10 | 8500 | | | | | | | | | | | | | | | | | |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.