

# FARM SPECIAL

|                     |                  |
|---------------------|------------------|
| <b>TIRE SIZE</b>    | <b>12.4 - 28</b> |
| <b>UM</b>           | IS STANDARD      |
| <b>CONSTRUCTION</b> | ⊠ BIAS           |
| <b>MACHINERY</b>    | TRACTOR          |
| <b>VERSION</b>      | STANDARD         |
| <b>TIRE TYPE</b>    | TT               |
| <b>LI/SS</b>        | 123 A6           |



## DIMENSIUNI IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 315  | <b>RIM REC</b> | W 11            |
| <b>OD (MM)</b>  | 1265 | <b>RIM ALT</b> | W 9; W 10       |
| <b>SLR (MM)</b> | 589  | <b>ECE</b>     | E11-106R-005533 |
| <b>RC (MM)</b>  | 3853 | <b>PR</b>      | 8               |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.30</b> |
| 30                | 1550        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.