


# AGRIMAX SPARGO

**VF 380/85 R 38**

<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRAKTÖR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	161 D



## UNDEFINED US STANDARD

<b>USA CODE</b>	94045303	<b>RC (IN)</b>	190.2
<b>SW (IN)</b>	15.0	<b>RIM REC</b>	W 13 A
<b>OD (IN)</b>	63.1	<b>RIM ALT</b>	W 12
<b>SLR (IN)</b>	28.7	<b>ECE</b>	E4-106R-001482

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	20	23	26	29	32	35	38	41	44	46
45	5470	6120	6670	7050	7320	7600	7880	8250	8620	8900	9270
FROM 40 TO 25	6010	6730	7350	7750	8050	8360	8670	9080	9480	9790	10200
20	6130	6860	7480	7900	8210	8530	8830	9250	9660	9980	10400
12	6250	6990	7630	8060	8370	8690	9010	9440	9860	10180	10610
5	6620	7400	8070	8510	8860	9190	9530	9980	10420	10760	11210

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.