

# FARM HIGHWAY TOUGH

|                     |                                                                 |
|---------------------|-----------------------------------------------------------------|
| <b>TIRE SIZE</b>    | 10.00 - 15 F1                                                   |
| <b>UM</b>           | US STANDARD                                                     |
| <b>CONSTRUCTION</b> | BIAS                                                            |
| <b>MACHINERY</b>    | MAȘINI DE IMPLEMENTARE /<br>REMORCĂ / MAȘINI DE<br>IMPLEMENTARE |
| <b>VERSION</b>      | STANDARD                                                        |
| <b>TIRE TYPE</b>    | TL                                                              |
| <b>LI/SS</b>        | 128 J                                                           |



## DIMENSIUNI US STANDARD

|                 |          |            |                 |
|-----------------|----------|------------|-----------------|
| <b>USA CODE</b> | 94044733 | <b>ECE</b> | E11-54R-0017870 |
| <b>SW (IN)</b>  | 10.8     | <b>PR</b>  | 8               |
| <b>OD (IN)</b>  | 33.6     |            |                 |
| <b>RIM REC</b>  | 8 LB     |            |                 |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>60</b> |
| 62               | 3960      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.